


HYM - SEED		
Specification	N.W.	9.5kg
	G.W. (Inner Box)	10.8kg
	G.W. (Outer Box)	11.7kg
	Unit Dimension	380*350*250mm
	Packing Dimension (Inner Box)	470*445*350mm
	Packing Dimension (Outer Box)	490*470*370mm
	Package Content	SEED*1 + Adaptor*1 + Remote Control*1 + Platter*1 + Slip Mat*1 + Counterweight*1 + User Manual*1
	Body material	wooden product
	Adaptor	DC 20V / 4.5A
Platter	Motor	CNC DC motor supports 33 rpm / 45 rpm
	Driving Method	Belt drive
	Speed	33 1/3rpm、 45rpm
	Turntable Platter	Aluminum alloy, 1.0kg
	Suspension System	Patented suspension system
	Wow and Flutter	Wow < 0.5% Flutter < 0.1%
	S/N	95dB (Digital) / 75dB (Vinyl)
Tonearm	Type	9 inch static balanced straight tonearm
	Overhang	18mm
	Pivot to Spindle distance	200mm
	Effective length	218mm
	Offset Angle	24.8°
	Null Points	62.5mm, 120.38mm
	Tracking Distortion	≤0.8%
	Tonearm lifter	Damping buffer
Tracking force adjustment method	Tail-end counterweight displacement adjustment	
Cartridge (AT-3600L)	Type	Moving magnetic cartridge
	Stylus	Diamond stylus
	Cartridge Weight	5.00±0.3gr
	Tracking force	3.5±0.5gr
	Load impedance	47KΩ
	Load capacitance	100pF
	Output Voltage	2.5mV ±3dB at 1KHz 3.54cm/sec
	Channel Separation	At 1kHz 18dB or more
	Channel Balance	2.5dB or less at 1kHz
Frequency Response	Value at 10KHz 0±3dB Based on Value at 1KHz	
Amplifier	Amplifier power	25W*2 Mid-Bass +10W*2 Treble
Speaker	Speaker Unit	Treble 2*1 inch 8Ω, Mid-Bass: 2*4 inch 4Ω
	Channel	2.0
	Frequency Range	55Hz - 20KHz
Bluetooth	Bluetooth module	2.4 GHz, BT 4.0
Audio output	3.5 Audio Output Level	RCA: LP 200mV Bluetooth: 500mV
AUX	AUX Output Level	≤1.0 V
Certificate	International Safety Certificate	CE, RoSH, BQB, FCC, CCC, WEEE, PSE, KC